

## ➤ Features

- Size 0.20\*0.18 inch /5.0\*4.5 mm
- RoHS compliant, lead-free and halogen-free
- Fast response to fault current
- Low resistance
- Low profile
- Compatible with high temperature solders

## ➤ Applications

- Computer, Mobile phones, Multimedia
- Automotive, Industrial controls, Telephony and broadband
- Game machines, Portable electronics, Battery

## ➤ Electrical Characteristics (25°C)

| Part Number      | $I_{hold}$ | $I_{trip}$ | $V_{max}$          | $I_{max}$ | $P_d$ typ | Time to trip |       | $R_{min}$ | $R_{1max}$ |
|------------------|------------|------------|--------------------|-----------|-----------|--------------|-------|-----------|------------|
|                  | (A)        | (A)        | (V <sub>dc</sub> ) | (A)       | (W)       | (A)          | (Sec) | (Ω)       | (Ω)        |
| BSMD2018-030-60V | 0.30       | 0.60       | 60                 | 10        | 1.2       | 1.50         | 3.00  | 0.50      | 2.30       |
| BSMD2018-050-60V | 0.55       | 1.20       | 60                 | 10        | 1.2       | 2.50         | 3.00  | 0.20      | 1.00       |
| BSMD2018-075-60V | 0.75       | 1.50       | 60                 | 10        | 1.2       | 8.00         | 0.30  | 0.11      | 0.63       |
| BSMD2018-100-15V | 1.10       | 2.20       | 15                 | 35        | 1.2       | 8.00         | 0.40  | 0.06      | 0.36       |
| BSMD2018-100-33V | 1.10       | 2.20       | 33                 | 35        | 1.2       | 8.00         | 0.40  | 0.06      | 0.36       |
| BSMD2018-150-15V | 1.50       | 3.00       | 15                 | 35        | 1.2       | 8.00         | 0.80  | 0.05      | 0.17       |
| BSMD2018-200-10V | 2.00       | 4.00       | 10                 | 35        | 1.2       | 8.00         | 2.40  | 0.03      | 0.10       |
| BSMD2018-260-24V | 2.60       | 5.00       | 24                 | 40        | 1.6       | 8.00         | 5.00  | 0.025     | 0.075      |
| BSMD2018-300-16V | 3.00       | 5.00       | 16                 | 40        | 1.6       | 8.00         | 10.00 | 0.015     | 0.048      |
| BSMD2018-500-6V  | 5.00       | 10.00      | 6                  | 100       | 2.0       | 25.00        | 2.00  | 0.005     | 0.025      |

## ➤ Vocabulary


- I<sub>hold</sub>** = Hold current: maximum current device will pass without tripping in 25°C still air.
- I<sub>trip</sub>** = Trip current: minimum current at which the device will trip in 25°C still air.
- V<sub>max</sub>** = Maximum voltage device can withstand without damage at rated current (**I<sub>max</sub>**).
- I<sub>max</sub>** = Maximum fault current device can withstand without damage at rated voltage (**V<sub>max</sub>**).
- P<sub>d typ.</sub>** = Typical power dissipated from device when in the tripped state at 25°C still air.
- R<sub>min</sub>** = Minimum resistance of device in initial (un-soldered) state.
- R<sub>1max</sub>** = Maximum resistance of device at 25°C measured one hour after tripping or reflow soldering of 260°C for 20 sec.

**Caution: Operation beyond the specified ratings may result in damage and possible arcing and flame.**


## ➤ Warning

- Users shall independently assess the suitability of these devices for each of their applications.
- Operation of these devices beyond the stated maximum ratings could result in damage to the devices and lead to electrical arcing and/or fire.
- These devices are intended to protect against the effects of temporary over-current or over-temperature conditions and are not intended to perform as protective devices where such conditions are expected to be repetitive or prolonged in duration.
- Exposure to silicon-based oils, solvents, electrolytes, acids, and similar materials can adversely affect the prolonged of these PPTC devices.
- These devices undergo thermal expansion under fault conditions, and thus shall be provided with adequate space and be protected against mechanical stresses.
- Circuits with inductance may generate a voltage ( $L di/dt$ ) above the rated voltage of the PPTC device.

➤ **Thermal Derating Curve**



➤ **Average Time-Current Curve**



A=BSMD2018-030  
B=BSMD2018-050  
C=BSMD2018-075  
D=BSMD2018-100  
E=BSMD2018-150  
F=BSMD2018-200


## ➤ Thermal Derating Chart

| Part Number  | Ambient operating temperature hold current( $I_{hold}$ ) |       |      |      |      |      |      |      |      |
|--------------|--|-------|------|------|------|------|------|------|------|
|              | -40°C  | -20°C | 0°C  | 25°C | 40°C | 50°C | 60°C | 70°C | 85°C |
| BSMD2018-030 | 0.48   | 0.42  | 0.35 | 0.30 | 0.24 | 0.21 | 0.17 | 0.15 | 0.10 |
| BSMD2018-050 | 0.87   | 0.77  | 0.67 | 0.55 | 0.46 | 0.41 | 0.36 | 0.31 | 0.23 |
| BSMD2018-075 | 1.19   | 1.05  | 0.91 | 0.75 | 0.61 | 0.54 | 0.47 | 0.41 | 0.32 |
| BSMD2018-100 | 1.71   | 1.52  | 1.32 | 1.00 | 0.94 | 0.84 | 0.74 | 0.64 | 0.50 |
| BSMD2018-150 | 2.38   | 2.10  | 1.82 | 1.50 | 1.27 | 1.13 | 0.99 | 0.85 | 0.64 |
| BSMD2018-200 | 2.95   | 2.65  | 2.35 | 2.00 | 1.74 | 1.59 | 1.44 | 1.29 | 0.98 |
| BSMD2018-260 | 3.82   | 3.46  | 3.06 | 2.60 | 2.24 | 2.03 | 1.82 | 1.60 | 1.26 |
| BSMD2018-300 | 4.40   | 3.96  | 3.52 | 3.00 | 2.65 | 2.43 | 2.20 | 1.96 | 1.59 |
| BSMD2018-500 | 7.29   | 6.57  | 5.86 | 5.00 | 4.38 | 4.02 | 3.66 | 3.26 | 2.66 |

## ➤ Environmental Specifications

| Test   | Conditions                  | Resistance change |
|--|-----------------------------|-------------------|
| Passive aging  | +85°C, 1000 hours           | ±5% typical       |
| Humidity aging   | +85°C, 85% R.H. , 168 hours | ±5% typical       |
| Thermal shock  | +85°C to -40°C, 20 times    | ±33% typical      |
| Resistance to solvent  | MIL-STD-202,Method 215      | No change         |
| Vibration  | MIL-STD-202,Method 201      | No change         |
| Ambient operating conditions : - 40 °C to +85 °C                         |                             |                   |
| Maximum surface temperature of the device in the tripped state is 125 °C |                             |                   |

➤ **Soldering Parameters**




| Profile Feature  | Pb-Free Assembly                 |
|--|----------------------------------|
| Average Ramp-Up Rate( $T_{s_{max}}$ to $T_p$ )   | 3°C/second max                   |
| Preheat<br>-Temperature Min( $T_{s_{min}}$ )<br>-Temperature Max( $T_{s_{max}}$ )<br>-Time( $T_{s_{min}}$ to $T_{s_{max}}$ ) | 150°C<br>200°C<br>60~180 seconds |
| Time maintained above:<br>-Temperature( $T_L$ )<br>-Time( $t_L$ )  | 217°C<br>60~150 seconds          |
| Peak Temperature( $T_p$ )  | 260°C                            |
| Ramp-Down Rate   | 6°C/second max                   |
| Time 25°C to Peak Temperature  | 8 minutes max                    |
| Storage Condition  | 0°C~30°C, 30%-60%RH              |

- Recommended reflow methods: IR, vapor phase oven, hot air oven, N<sub>2</sub> environment for lead-free.
- Recommended maximum paste thickness is 0.25mm.
- Devices can be cleaned using standard industry methods and solvents.

**Note 1:** All temperature refer to topside of the package, measured on the package body surface.


**Note 2:** If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

➤ **Physical Dimensions & Recommended Pad Layout (mm)**




| Part Number      | Marking | Quantity | A    |      | B    |      | C    |      | D    | E    |
|------------------|---------|----------|------|------|------|------|------|------|------|------|
|                  |         |          | Min  | Max  | Min  | Max  | Min  | Max  | Min  | Min  |
| BSMD2018-030-60V | B030    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-050-60V | B050    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-075-60V | B075    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-100-15V | B100    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-100-33V | B100    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-150-15V | B150    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-200-10V | B200    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-260-24V | B260    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-300-16V | B300    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |
| BSMD2018-500-6V  | B500    | 1500     | 4.72 | 5.44 | 4.22 | 4.93 | 0.50 | 1.20 | 0.30 | 0.25 |

➤ **Tape And Reel Specifications (mm)**



| Governing Specifications | BSMD2018-030~<br>BSMD2018-075 | BSMD2018-100~<br>BSMD2018-150 | BSMD2018-200~<br>BSMD2018-500 |
|--------------------------|-------------------------------|-------------------------------|-------------------------------|
| W                        | 12.0 ± 0.3                    | 12.0 ± 0.3                    | 12.0 ± 0.3                    |
| F                        | 5.5 ± 0.05                    | 5.5 ± 0.05                    | 5.5 ± 0.05                    |
| E <sub>1</sub>           | 1.75 ± 0.1                    | 1.75 ± 0.1                    | 1.75 ± 0.1                    |
| D <sub>0</sub>           | 1.55 ± 0.05                   | 1.55 ± 0.05                   | 1.55 ± 0.05                   |
| D <sub>1</sub>           | 1.55 <sub>min</sub>           | 1.55 <sub>min</sub>           | 1.55 <sub>min</sub>           |
| P <sub>0</sub>           | 4.0 ± 0.1                     | 4.0 ± 0.1                     | 4.0 ± 0.1                     |
| P <sub>1</sub>           | 8.0 ± 0.1                     | 8.0 ± 0.1                     | 8.0 ± 0.1                     |
| P <sub>2</sub>           | 2.0 ± 0.05                    | 2.0 ± 0.05                    | 2.0 ± 0.05                    |
| A <sub>0</sub>           | 3.58 ± 0.1                    | 3.58 ± 0.1                    | 3.58 ± 0.1                    |
| B <sub>0</sub>           | 4.93 ± 0.1                    | 4.93 ± 0.1                    | 4.93 ± 0.1                    |
| T                        | 0.2 ± 0.1                     | 0.2 ± 0.1                     | 0.2 ± 0.1                     |
| K <sub>0</sub>           | 0.74 ± 0.1                    | 1.04 ± 0.1                    | 1.35 ± 0.1                    |
| Leader <sub>min</sub>    | 390                           | 390                           | 390                           |
| Trailer <sub>min</sub>   | 160                           | 160                           | 160                           |

| Reel Dimensions |             |
|-----------------|-------------|
| C               | φ178 ± 1.0  |
| D               | φ60.2 ± 0.5 |
| H               | 16.0 ± 0.5  |
| W               | 13.2 ± 1.5  |



➤ **Contact information**

SHENZHEN BHFUSE INDUSTRIAL CO., LTD

TEL: 0755-85259917

E-MAIL: sales@bhfuse.com