



Model BSMD1206CF

File Number: E544319

COMPANY

SHENZHEN BHFUSE INDUSTRIAL CO LTD

A1202, Building 7, Phase II, Dongjiu Innovation and Technology Park
No. 73 Xiali South Road, Xia Li Lang Community
Nanwan Street, Longgang District
SHENZHEN, Guangdong 518114 China

MODEL INFO

BSMD1206CF
Supplemental micro fuses: surface mount

SUPPLEMENTAL FUSES	额定值
Micro Fuse	Yes
Pigtail Leads	No
Surface Mount	Yes
Cartridge Enclosed	No
Time Delay	No
Paper Tube	No
Filled Tube	No
OD - Length	3.2 mm
Length - Width	1.6 mm
Height	0.65 mm

RATING TABLE				
Amps Minimum (A)	Amps Maximum (A)	Voltage (V)	Voltage Source	Interrupting Rating (A)
0.1	50	24	dc	200
0.1	50	32	dc	200

RATING TABLE

Amps Minimum (A)	Amps Maximum (A)	Voltage (V)	Voltage Source	Interrupting Rating (A)
0.1	50	36	dc	200
0.1	30	24	dc	300
0.1	20	48	dc	150
0.1	7	63	dc	50
0.1	7	72	dc	50
0.1	3	80	dc	50
0.1	3	100	dc	50
0.1	3	110	dc	50
0.1	3	125	dc	50

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明： "©2024 UL LLC."